

A versatile and innovative tree climbing lanyard that integrates the exclusive **Gyro swivel** for exceptional freedom of movement. For use on front or side attachment points.

The retrieving pulley features a minimal design and is equipped with a built-in secondary attachment point.

Soft 8 mm polyester-aramid cord integrates with the rope for smooth, precise, and secure length adjustment.

Pre-assembled with a Michoacan hitch, also certified with the Catalyst and Distel for the best possibility of customization.

The Iridium 11 mm Heatcore polyamide rope with exclusive **CRT (Compact Rope Termination)** loops delivers long-lasting ease of handling, durability and robustness thanks to the Heatcore technology that joins the sheath and core.

High visibility colors.

The adjustment system can be disassembled by the user (Torx T20 allen wrench included) to replace the rope and the cord.

348401 GYRO LANYARD SINGLE + 2x2125 2 m

348402 GYRO LANYARD SINGLE + 2x2125 3.5 m

348403 GYRO LANYARD SINGLE + 2x2125 5 m



Ref.	Product name Nombre del producto	Weight Peso		CE EN 358	ANSI Z133:2017
		g	oz		
348401	GYRO LANYARD SINGLE + 2x2125 2 m	540	19.1	•	•
348402	GYRO LANYARD SINGLE + 2x2125 3.5 m	660	23.3	•	•
348403	GYRO LANYARD SINGLE + 2x2125 5 m	770	27.2	•	•

Ref. 3484

TREE CLIMBING, ROPE ACCESS, TEAM RESCUE

Soft **8 mm polyester-aramid cord** integrates with the rope for smooth, precise, and secure length adjustment

Pre-assembled with a **Michoacan** hitch, also certified with the **Catalyst** and **Distel** for the best possibility of customization

Exclusive **Gyro swivel** for exceptional freedom of movement



The **retrieving pulley** features a minimal design and is equipped with a built-in **secondary attachment point**

11 mm Heatcore Rope: polyamide rope delivers long-lasting ease of handling, durability and robustness thanks to the Heatcore technology that joins the sheath and core. High visibility colors

CRT - Compact Rope Termination



Ref. 3484

TREE CLIMBING, ROPE ACCESS, TEAM RESCUE

The adjustment system can be disassembled by the user (Torx T20 allen wrench included) to replace the rope and the cord.



GYRO LANYARD SPARE ROPE

351601 2 m

351602 3.5 m

351603 5 m

351604 7 m

351605 10 m

Replacement ropes for the Gyro Lanyards.



GYRO LANYARD SPARE CORD

3518

Replacement hitch cord for the Gyro Lanyards.



VENTRAL ATTACHMENT USE

Doubled mode

Single mode

EN 795

FIG. 10

ONLY PARKING
NO SAFETY

MIN
160 mm

Single mode

OVAL XL 3LOCK
ref. 2125

LATERAL ATTACHMENT USE

Lateral mode